



BE-8004

4Ch H.264 Standalone DVR System



- H.264 Stand-alone DVR
- 4Ch Audio & Video Input
- Video Total Frame Rate: 100fps, PAL
- 25fps per Channel, real-time
- High Image quality.
- Pentaplex: Live / Record / Playback / Network / Mobile Phone
- User friendly Menu, Settings and Remote.
- Support Host USB backup
- Recording resolution up to 720x480 D1 resolution
- Adjustable VGA resolution setting
- One Channel or Multi Channel video backup capability
- High speed network transmission
- Accommodates 1 SATA HDD (max.)
- Search: Calendar and Log file.
- Built-in File viewer on copy media
- Supports Static & Dynamic IP



Specifications:

Video Format		NTSC	PAL
Video Input		4 Ch Input / BNC	
Audio Input		4 Ch Input / RCA	
Video Output		1CH Output / BNC	
Audio Output		1CH Output / RCA	
XGA Output		640x480、800x600、1024x768、1280x1024、1440x900	
Alarm Input		4CH Alarm In	
Alarm Output		Buzzer、1 x Relay Out (N.O、N.C)	
Display Mode		Full Screen, 4CH Split Screen, Auto Switch	
Display Resolution		720 x 480	720 x 576
Recording Resolution	Highest	720 x 480	720 x 576
	High	720 x 240	720 x 288
	Normal	360 x 240	360 x 288
Recording Frame		Max. 120 FPS	Max. 100 FPS
Compression Algorithm		H.264	
Operating System		Embedded Linux	
Pentaplex		Live / Record / Playback / Network / Mobile Phone	
Recording Mode		Manual, Schedule, Event	
Schedule Recording		Full Recording, Motion, Alarm, Manual Recording	
Status Indicator		Power, Recorder, Play	
Event Mode		Alarm Trigger, Motion Trigger, Video Loss Recording Duration: 10~60 sec.	
Playback Mode		Normal Speed: x1	
		Fast Forward: x2 / x4 / x8 / x16 multiple speed	
		Slow Forward: 1/2、1/4、1/8 multiple speed	
		Fast Rewind: x2 / x4 / x8 / x16	
		Frame by Frame Playback: Forward	
		Search Function: Time / Event	
Network Protocol		TCP/IP / PPPoE / DHCP / SMTP / DDNS	
HDD Type		SATA 3.5"HDD x 1 (No HDD Included)	
HDD Management		Automatic Format System	
PTZ Control		Communication Protocol (PELCO P, PELCO D, MIKAMI)	
Backup Device		USB 2.0 Flash Memory Stick	
Firmware Update		Host USB	
Multi-Language		English / Chinese / Others	
Control Mode		Front Panel / Remote Control / USB Mouse / Internet	
Network Control		IE Browser	
Network Function		Live Display / Playback / PTZ Control / System Setup	
Mobile Phone		IE browser supported for mobile-phone surveillance	
Power Supply		DC 12V / 3A(AC100V~240V 50/60HZ)	
Unit Dimension		220mm (W)x 288mm (D) x 48 mm (H)	
Weight		Unit Weight 1.6kg (HDD and Power Adapter Not Included)	
Operating Temperature		0℃ ~ 46℃	

